

# POST DRIVER



From the backyard to the back-forty, a Minuteman Gas Powered Post Driver will save you time and money on any fencing or staking project. Whether it be a chain-link fence, miles of T-Posts, misc. stakes or ground rod - The Minuteman saves significant time and effort over manual driving methods and is much safer to operate.



MINUTEMAN Fixed Handle



MINUTEMAN XL8
Extended Handle



## PRODUCT LINE FEATURES

- One-person, operation.
- Select Models Drive: T-Posts

Chain link fence posts (13/8", 15/8", 23/8" and 27/8")
Ground Rods
Form Pins
Ground Anchors
Round posts up to 3"

Safely drives posts without a ladder (Minuteman at 6' & Minuteman XL8 at 8').

**Tree Stakes** 

Ideal Driver weight - Let the tool do the work.

- Ductile body for durability and long life.
- 37.7 cc 4-stroke engine (no mixing) Easy recoil start.
- 3 Year Residential / 1 Year Commercial Warranty
- Vibration isolation system and comfort grip handle for extended operating time.
- Prompt Factory service.
- Ergonomically balanced for comfort and effortless driving.
- Includes patented break-away Adapters for ease of Driver alignment and removal.

# SAVETIME / SAVE MONEY / HASSLE-FREE / 3 YEAR WARRANTY\*



## **No More Hand Held Pounders**

Beating posts into the ground is exhausting and unsafe. Fatigue and repetitive force can cause operators to miss the post, increasing the potential for injury.



### **No More Digging Holes**

No need to dig below the frost line and deal with clean-up of excess soil -Standards show driven posts are equal in strength to cemented posts.



### **No More Concrete**

No digging, clean-up, mixing, or pouring - Driven posts can be installed 10-times faster, at a lower cost, and no drying time.

SPECIFICATIONS	MINUTEMAN	MINUTEMAN XL8
Scan for additional info		
Handle Design	Fixed	Rotating / Extended
Part Number	350001	350010
Master Chuck Tube I.D.	2.25" (57.1 mm)	3.25" (82.5 mm)
Drives Posts Up To	2" (50.8 mm)	3" (76.2 mm)
Unit Dimensions	11"W x 13.5"D x 24"H (280 x 343x 610 mm)	11"W x 17" D x 24" H (280 x 432 x 610 mm)
Unit Weight	46 lbs. (21 kg)	53 lbs. (24 kg)
Engine	4-stroke (No Mix), 37.7 cc	4-stroke (No Mix), 37.7 cc
BPM (beats per minute)	1720 (approximate)	1720 (approximate)
Post Installation without ladder**	6 ft. Tall Post	8 ft. Tall Post
Included Patented Adapters	1" for Ground Rod & Form Pin 1¾" for 15⁄8" Chain Link Line Posts	1¾" for 15/8" Chain Link Line Posts 2" for 17/8" Chain Link Line Posts 2½" for 23/8" Chain Link Terminal Posts

<sup>\* 3</sup> Year Residential / 1 Year Commercial Warranty





<sup>\*\*</sup> The ability to install posts without a ladder greatly shortens installation time and increases project safety